

Series	Bollard & Spike series			Additional Information	
Input Watt	9	6	12	System lumens (Lm/W)	> 140
Product Code	LD-55-9W	LD-12-6Ws	LD-12-12Ws	CRI	> 80
Led /Chip	4.5W	6W	12W	Input Voltage (AC)	120-300V
Led Rating Current (mA)	1.5A	180 mA	350 mA	Power Factor	>0.90
Number Of Leds	3	1	1	Surge Protection	Upto 3 KV
View Angle	90*	60*	60*	Driver Efficiency (%)	>70%
Color Temperature	3000K-6000K	3000K-6000K	3000K-6000K	Driver (Type)	Isolate
Lumens	900	600	1200	Driver Location	Internal
Input Current	40	25	50	IP (20/40/65)	IP65
Calculated Input current (@ 240 V)	42	28	56	BIS (IS Number)	IS 15885 (PART 2/SEC 13)
Output Current	700mA	140mA	280mA	BIS (R Number)	R-85001180
Output Voltage	9V	36V	36V	Led Life	> 50000 Hrs
Shape	Cylindrical	Spike	Spike	Operating Temperature	-10* to +50* C
Dimensions (Length - mm)	645	350	370	Rated Voltage (AC)	240V
Dimensions (Width - mm)	107.5	73	81.5	Frequency (Hz)	50Hz± 2
Dimensions (Height - mm)	107.5	60.5	65	Protection	Over Temperature, Short-circuit Protection, OC Protection, Reverse Polarity Protection
Dimensions (Cutout - mm)	NA	NA	NA		
BIS Model No.	LDS 6-10	LSF 06	LSF 12		
Packing	1	12	12		



Ledure Bulk Head Light series has excellent modern sconces can be divided into many types, from waterproof rated, it includes indoor wall light fixtures and exterior wall lights; from the appearance, it contains coach lights and plug in wall lights. Up shine wall mount light fixture usually designed with waterproof rubber ring for IP65 IP54 waterproof. You can install wall lights outdoor and indoor according to your environment. Safe and reliable LED wall mount light fixtures have aluminum heat sink, powder spray painting surface treatment, glossy and corrosion resistance. Interior modern sconces can easy install, widely used for corridor, stairway, basement, carport application.