

Series	Master Spot Lamp Series			Additional Information	
Input Watt	12	20	30	System lumens (Lm/W)	> 140
Product Code	LD-092-12W	LD-092-20W	LD-092-30W	CRI	> 80
Led /Chip	12	20	36	Input Voltage (AC)	90-320V
Led Rating Current (mA)	300	600	1000	Power Factor	>0.5
Number Of Leds	1	1	1	Surge Protection	Upto 3 KV
View Angle	60*	60*	60*	Driver Efficiency (%)	>65%
Color Temperature	3000K-6000K	3000K-6000K	3000K-6000K	Driver (Type)	Isolate CC
Lumens	1200-1320	2000-2200	3000-3300	Driver Location	External
Input Current	52 mA	86 mA	130 mA	IP (20/40/65)	IP20
Calculated Input current (@ 240 V)	53	88	132	BIS (IS Number)	IS 15885 (PART 2/SEC 13)
Output Current	280 mA	480 mA	710 mA	BIS (R Number)	R-85001180
Output Voltage	36V	36V	36V	Led Life	> 50000 Hrs
Shape	NA	NA	NA	Operating Temperature	-10* to +50* C
Dimensions (Length - mm)	ø74	ø92	ø98	Rated Voltage (AC)	240V
Dimensions (Width - mm)	N.A	N.A	N.A	Frequency (Hz)	50Hz± 2
Dimensions (Height - mm)	90	116	132	Protection	Over Temperature, Short-circuit Protection, OC Protection, Reverse Polarity Protection
Dimensions (Cutout - mm)	N.A	N.A	N.A		
BIS Model No.	LTL 12	LTL 20	LTL 30		
Packing	12	12	12		



Ledure Master Spot Lamp series is an ideal retrofit surface mounted solution for spot and general lighting application.

A uniquely designed LED Spot Light to brighten up your home in style – 360° Rotating COB With 90° Flexible Folding to softly highlight the features of your thoughtfully designed interiors. Ledure Master Spot Lamp Widely used for interior decoration such as at home, hotel, clubs, showroom & shopping mall.