

Series	Shine Downlight						
Input Watt	3	5	7	9	12	Additional Information	
Product Code	LD-38-3W	LD-38-5W	LD-38-7W	LD-38-9W	LD-38-12W	System lumens (Lm/W)	> 140
Led /Chip	0.5	0.5	1	1	1	CRI	> 80
Led Rating Current (mA)	30	30	60	60	60	Input Voltage (AC)	120-300V
Number Of Leds	14	14	15	15	23	Power Factor	>0.90
View Angle	120*	120*	120*	120*	120*	Surge Protection	>3KV
Color Temperature	3K,4K,,6K,R,G,B,P	3K,4K,,6K,R,G,B,P	6000K	3000K-6000K	6000K	Driver Efficiency (%)	>85%
Lumens	300	375	490	560-630	950	Driver (Type)	Non-Isolate
Input Current	11	19	26	34	45	Driver Location	Internal
Calculated Input current (@ 240 V)	14	23	32	42	56	IP (20/40/65)	IP20
Output Current						BIS (IS Number)	IS 10322 (PART 5/ SEC 2)
Output Voltage	252	252	270	270	270	BIS (R Number)	R-93006297
Shape	Round	Round	Round	Round	Round	Led Life	> 50000 Hrs
Dimensions (Length - mm)	Ø80	Ø112	Ø112	Ø112	Ø115	Operating Temperature	-10* to +50* C
Dimensions (Width - mm)	Ø80	Ø112	Ø112	Ø112	Ø115	Rated Voltage (AC)	240V
Dimensions (Height - mm)	36	55	55	55	55	Frequency (Hz)	50Hz± 2
Dimensions (Cutout - mm)	40	75	75	75	84	Protection	Over Temperature, Short-circuit Protection, OC Protection, Reverse Polarity Protection
BIS Model No.	DLHD3	3DLBD-5W	3DLBD-7W	3DLBD-9W	4D12W		
Packing	60	60	60	60	20		

LD-38-3W



Ledure Shine Downlights comes with extensive range of Led downlights include solutions for all commercial applications that are energy efficient. Ledure Shine downlights are equipped with backlit Led formation for brighter solution. Shine Downlights Anti glare diffuser features give eye comfort .This product available in wide range for all junction /concealed box sizes. Ledure Shine downlights are best to be used at Lobby, Corridor , Restaurant, Hotels , Retail outlet , Jewellery showroom, Mall & Multiplexes, Resident villas & offices.