Uromax Series

LEDURE

Series	Uro Max Series						Additional Information	
Input Watt	3	5	7	9	12	15	System lumens (Lm/W)	> 140
Product Code	LD-31-3W	LD-31-5W	LD-31-7W	LD-31-9W	LD-31-12W	LD-31-15W	CRI	> 80
Led /Chip	0.5	0.5	1	1	1	1	Input Voltage (AC)	120-300V
Led Rating Current (mA)	30	30	60	60	60	60	Power Factor	>0.90
Number Of Leds	14	14	14/15	15	23	40	Surge Protection	>3KV
View Angle	240*	240*	240*	240*	240*	180*	Driver Efficiency (%)	>85%
Color Temperature	6000K	6000K	6000K	6000K	6000K	6000K	Driver (Type)	Non-Isolate
Lumens	270	450	630	810	1080	1350	Driver Location	Internal
Input Current	11	19	26	34	45	56	IP (20/40/65)	IP20
Calculated Input current (@ 240 V)	14	23	32	42	56	69	BIS (IS Number)	IS 16102 (PART 1)
Output Current							BIS (R Number)	R-85001171
Output Voltage	252	252	252	270	270	270	Led Life	> 50000 Hrs
Shape	A55-240D	A55-240D	A55-240D	A60-240D	A65-240D	A65-120D	Operating Temperature	-10* to +50* C
Dimensions (Length - mm)	Ø55	Ø55	Ø55	Ø60	Ø65	Ø65	Rated Voltage (AC)	240V
Dimensions (Width - mm)	Ø55	Ø55	Ø55	Ø60	Ø65	Ø65	Frequency (Hz)	50Hz± 2
Dimensions (Height - mm)	106	106	106	110	131	131	Protection	Over Temperature, Short-circuit Protection, OC Protection, Reverse Polarity Protection
Dimensions (Cutout - mm)	NA	NA	NA	NA	NA	NA		
BIS Model No.	ON3W	ON5W	LN7W	LN9W	ON12W	ON15W		
MRP(RS)	130	140	150	175	200	250		
Packing								

Ledure Uromax lamps comes with a patented technology which makes it energy efficient & long lasting .Ledure Uromax Series feature beautiful light that provides exceptional color quality, making the colors in your home appear vibrant, rich & natural. This series products are with High beam angle 270 degree along with retro fit B-22 caps. This product is made to last as per the Indian working condition. Uromax Series are good for use anywhere you would use a traditional light bulb, even in a fully enclosed Luminaires or fancy lights. Ledure Uromax Lamp series are the best lighting solution for Living room , corridors , shops , offices , staircase & warehouse.